



T75561▲ **T75661▲**


Submitted Model No.:_____

Specific Features: _____



▲ Designate Proper Finish Suffix

RP90545▲ Available Thick Wall Installation Kit



BRIZO®

INTEGRATED SHOWER DIVERTER TRIM

- Rook™ Valve Trim with Three Function Diverter (T75561)
- Rook™ Valve Trim with Six Function Diverter (T75661)
- Three Lever Handles

FEATURES:

- *TempAssure® Thermostatic valve trim*
- *Three or six function diverter trim*

STANDARD SPECIFICATIONS:

- *Main control utilizes Thermostatic Valve cartridge*
- *Thermostatic wax element maintains the outlet temperature to ±3.6˚F*
- *For use with MultiChoice® Universal integrated shower diverter rough valve body (R75000 Series)*
- *Back-to-back installation capability*
- *Top handle controls diverter functions*
- *Bottom (2) handles control volume and temperature*
- *Field adjustable to limit bottom handle rotation into hot water zone*
- *Bottom handle 90° Maximum rotation*
- *Graphics indicate hot/cold temperature adjustment*
- *Three function diverter for 2 individual positions, 1 shared position*
- *For two individual functions, no shared functions, order additional RP72123*
- *Six function diverter for 3 individual positions, 3 shared positions*
- *For three individual functions, no shared functions, order additional RP72124*
- *1/2" rough-in*
- *Cartridges included*
- *Standard installation allows up to 1-1/8" finished wall thickness*
- *Thick wall installation kit (RP90545▲) can be ordered to allow for up to 2-1/8" finished wall thickness*

WARRANTY

- *Lifetime limited warranty on parts (other than electronic parts and batteries) and finishes: or, for commercial users, for 5 years from date of purchase.*
- *5 year limited warranty on electronic parts (other than batteries); or, for commercial users, for 1 year from the date of purchase. No warranty is provided on batteries.*

COMPLIES WITH:

- *ASME A112.18.1 / CSA B125.1*

Indicates compliance to ICC/ANSI A117.1

Maximum Flow Rate Guide

Rough	Cartridge	Outlet	40 psi	60 psi	80 psi
R75000	TempAssure® Thermostatic	Shower	5.9 gpm	7.2 gpm	8.3 gpm
R75000-WS	TempAssure® Thermostatic	Shower	5.3 gpm	6.5 gpm	7.4 gpm

Based on 6 Setting Diverter

Brizo Kitchen & Bath Company reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.brizo.com for finish options and product availability.

Brizo Kitchen & Bath Company
Indianapolis, Indiana 46280
A Division of Masco Corporation of Indiana
© 2018 Brizo Kitchen & Bath Company