

Pressure Balance Bath/Shower Trim with Double Ceramic Pressure Balance Cartridge

MODEL NUMBER:

TRIM KITS:


- ☐ TU105502 Studio S Bath/Shower Trim Kit with Pressure Balance Cartridge

 Metal lever handle. LESS valve body.
- ☐ TU105501 Studio S Shower ONLY Trim Kit with Pressure Balance Cartridge

 Metal lever handle. LESS valve body.
- ☐ TU105500 Studio S Valve ONLY Trim Kit with Pressure Balance Cartridge

 Metal lever handle. LESS valve body.

For use with Flash™ Rough Valve Bodies



TU105502 Bath/Shower Trim Shown

GENERAL DESCRIPTION:

Double Ceramic Pressure Balance Cartridge: Features one-piece design with ceramic discs and ceramic balancing spool. Includes integrated check valves and hot limit safety stop. Cartridge is back to back capable. Ceramic balancing spool maintains constant output temperature in response to changes in relative hot and cold supply pressure. Washerless ceramic discs provide smooth handle movement and are unaffected by harsh water conditions.

Trim: Features 8" brass rain showerhead with a maximum 2.5 gpm/9.5 L/min. flow rate. Metal slip-on diverter spout. Metal wall valve trim with metal lever.

PRODUCT FEATURES

One-Piece Cartridge: Simplifies installation and maintenance.

Double Ceramic Pressure Balance Cartridge:

Combination of Ceramic Disc Mixing Valve and a Ceramic Balancing Spool in a one-piece cartridge.

Ceramic Disc Mixing Valve: Assures a lifetime of drip-free performance and smooth handle operation.

Ceramic Balancing Spool: Maintains a constant output temperature in response to changes in relative hot and cold supply pressure. Ceramic material is unaffected by mineral deposits and harsh water conditions.

Integrated Check Valves: Engineered to eliminate cross flow.

Adjustable Hot Limit Safety Stop: Limits the amount of hot water allowed to mix with cold. Reduces the risk of accidental scalding.

Comfort Zone: Offers a wider shower range to fine tune the desired temperature within the useful temperature zone.

Back-to-Back Capability: Hot and cold can be reversed quickly and easily.

1-5/8" TO 3-1/4" (41 TO 83 mm) FINISHED WALL 1/2" (12 mm) NPT 2-1/8"_ 4-1/2 (54 mm) 1-5/8" TO 3-1/4" (41 TO 83 mm) (203 mm) OPTIONAL TO FINISHED 74" (1880 mm) FLOOR USUALLY BETWEEN 65" AND 80" 11-7/8" (301 mm) REF. FOR HEAD CLEARANCE (1651 AND 2032 mm) ก์∏ิ 7-1/2" DIA (185 mm) 18" (457 mm) OPTIONAL 2-3/4" MAX. (69 mm) 1-3/4" MIN. (45 mm) 1-1/2" RFF (38 mm) 6-1/8" REF. (155 mm) 1/2" (13 mm) TOP OF TUB RIM . COPPER BOTTOM OF TUB

SUGGESTED SPECIFICATION

Bath/shower fitting shall feature brass rain showerhead with Max. 2.5 gpm/9.5 L/min. flow rate. Shall feature double ceramic pressure balance cartridge which is capable of back-to-back installation. Cartridge shall feature integrated check valves to eliminate cross flow. Capable of meeting ASSE1016 @1.3gpm. Cartridge shall also feature hot limit safety stop. Fitting shall be: American Standard - Trim Kit Model # TU18450 . and Flash Valve Body Model # RU10

© 2018 AS America, Inc. 8/18



Studio[®]S


Pressure Balance Bath/Shower Trim

with Double Ceramic Pressure Balance Cartridge

CODES AND STANDARDS

These products meet or exceed the following codes and standards:

ASSE 1016 / ASME A112.18.1016 / CSA B125.16 ASME A112.18.1 / CSA B125.1 Rated to meet ASSE 1016 @ 1.3gpm



				Finish Options		
TRIM KITS *	Product			Polished Chrome	Matte Black	PVD Brushed Nickel
	Number	Description		002	243	295
	TU105502	Bath/Shower Trim Kit. Metal lever handle. Brass rain showerhead. LESS valve body.				
F	TU105501	Shower Only Trim Kit. Metal lever handle. Brass rain showerhead. LESS valve body.	(<u>B</u>)			
	TU105500	Valve Only Trim Kit. Metal lever handle. LESS valve body.	(A)			

* TRIM & ROUGH MUST BE ORDERED SEPARATELY.

DIES	Product Description	Without Screwdriver Stops	With Screwdriver Stops
BO	Rough Valve Body. Universal* inlets/outlets.	RU101	RU101SS
VE.	Rough Valve Body. Stub-out inlets/outlets for Press-Fit Fittings.	RU102	RU102SS
UGH VAL	Rough Valve Body. PEX inlets/Universal outlets for Crimp Ring PEX system (ASTM F1807).	RU107	RU107SS
	Rough Valve Body. PEX Elbow inlets/Universal outlets for Crimp Ring PEX system (ASTM F1807).	RU107E	RU107ESS
™ RO	Rough Valve Body. PEX inlets/Universal outlets for Cold Expansion PEX system (ASTM F1960).	RU108	RU108SS
Flash™	Rough Valve Body. PEX Elbow inlets/Universal outlets for Cold Expansion PEX system (ASTM F1960).	RU108E	RU108ESS
	Rough Valve Body. CPVC inlets/Universal outlets.	RU109	RU109SS

TIONAL	Product Number	Product Description
ACC	M054905 0070A	Deep Rough-In Kit

ÁD4

Meets the American Disabilities Act Guidelines and **ANSI A117.1** Requirements for the physically challenged.

PART OF LIXIL

© 2018 AS America, Inc. 8/18