

Submitted Model No.:

Specific Features:

Min. 2 1/2" (64 mm) Clearance to Back Splash 5 1/16" (129 mm) 8 25/32" (223 mm) 9 25/32" (248 mm) 5 3/4" (146 mm) 2 5/8" (67 mm) Dia. -1 1/8" to 1 1/2" (29 mm to 38 mm) Hole Size Max. 3' (76 mm) 33" (838 mm) 34" (863 mm) 2 13/32" (61 mm) Dia. 2 13/32" (61 mm) Dia. 1 5/16" (33 mm) Dia. 2 13/32" (61 mm) Dia. 2 13/32" (61 mm) Dia. 1 5/8" (41 mm) Dia. 1 5/8' (41 mm) Dia. 1 5/8" (41 mm) Dia. 3 7/64' (76 mm) 2 13/32" (61 mm) Dia. 6 13/16" (173 mm) 6 39/64" (168 mm) 13/32' 6 39/64" (168 mm) (61 mm) Dia. 1 5/16" (33 mm) Dia. 1 5/16' (33 mm) -Dia. RP72411 grid strainer w/o overflow. Optional, not included. RP72412 grid strainer w/ overflow. Optional, not included. RP72413 pop-up strainer w/o overflow. Optional, not included. RP72414 pop-up strainer w/ overflow. Optional, not included

▲ Designate proper finish suffix

Brizo Kitchen & Bath Company reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or

BRIZO

LAVATORY FAUCET

- Charlotte[™] Collection
- Single Handle Deck Mount

FEATURES:

■ DIAMOND Seal® Technology

STANDARD SPECIFICATIONS:

- Max flow rate: 1.50 GPM @ 60 PSI, 5.68 L/Min @ 414 kPa
- Max flow rate (ECO models only): 1.20 GPM @ 60 PSI, 4.54 L/Min @ 414 kPa
- One hole mount
- Diamond coated ceramic cartridge
- 3/8" O.D. straight, staggered PEX supply lines
- Solid brass fabricated body
- Spout features hidden water-efficient laminar flow aerator


WARRANTY:

- Lifetime limited warranty on parts (other than electronic parts and batteries) and finishes: or, for commercial users, for 5 years from date of purchase.
- 5 year limited warranty on electronic parts (other than batteries); or, for commercial users, for 1 year from the date of purchase. No warranty is provided on batteries.



COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1
- ASME A112.18.2 / CSA B125.2



- EPA WaterSense®
- Verified compliant with 0.25% weighted average Pb content regulations