

AQUA FLO[®]

PLATINUM

Filter Housing Kits

Aqua Flo[®] Filter Housings are made to last, offering high-quality performance at economical prices. All housing kits are easy to install and come complete with a mounting bracket and hardware plus sump wrench for easy sump removal. Filter cartridges are sold separately.



FEATURES / BENEFITS:

- ◆ **Size** – Required flow rates and installation space will determine the size of the housing. Housings typically come in four sizes: 2.5" x 10", 2.5" x 20", 4.5" x 10", 4.5" x 20"
- ◆ **Material of Construction** – Reinforced Polypropylene
- ◆ **Valve-in-Head (26069 only)** – allows you to bypass or shut off the water during cartridge replacement.
- ◆ **Pressure Relief Button (Except 26069)** – relieves pressure from the housing prior to changing cartridge
- ◆ **Stainless Steel Threads (26069 only)** – reduces possibility of cross threading and allows for tighter pipe fit
- ◆ **Double O-Ring (Big Value 4.5" Housings Only)** – ensures added seal insurance protecting from leaks



Sump Wrench



Mounting Bracket and Hardware



Double O-Ring Seal
(Aqua Flo Platinum BV
Housings Only)



Pressure Relief Button



Valve-in-Head



Filter Housing Kits

- ◆ **Max. Water Temperature:** 40°C (100°F)
- ◆ **Min. Water Temperature:** 2°C (35°F)
- ◆ **Max. Water Pressure:** 100 psi (689 kPa)
- ◆ **Materials of Construction:** Reinforced Polypropylene (cap and blue sump)
- ◆ **Housing O-Ring:** EPDM
- ◆ **Pressure Relief Button:** Nylon (Except 26069)
- ◆ **Limited One Year Warranty**



P-H-PR-20BV



P-H-PR-20



P-H-PR-10BV



P-H-PR-10



WVIH34SS

SPECIFICATIONS & PERFORMANCE:

ITEM #	MODEL DESCRIPTION	FEATURES	FILTER SIZE (IN)	INLET/OUTLET SIZE NPT (IN)	COLOR	DIMENSIONS (WIDTH) X (HEIGHT) (IN)	WEIGHT (LBS)	REPLACEMENT ORING	WRENCH	CERTIFICATION
26069	HOUSING, WVIH34SS	VALVE-IN-HEAD, SS THREAD NO PRESSURE RELIEF	2.5" x 10"	3/4"	All Blue	5 x 13.5 (127mm x 343mm)	4	92060	26007	NR
36051	HOUSING, P-H-PR-10-3/4	PRESSURE RELIEF, SINGLE (1) O-RING	2.5" x 10"	3/4"	Blue / Black	5 x 12 (127mm x 305mm)	4	60010681 x 1	93016	NSF CERTIFIED
36273	HOUSING, P-H-PR-20-3/4	PRESSURE RELIEF, SINGLE (1) O-RING	2.5" x 20"	3/4"	Blue / Black	5 x 23 (127mm x 584mm)	7	60010560 x 1	93018	NSF CERTIFIED
36117	HOUSING, P-H-PR-10BV-3/4	PRESSURE RELIEF, DOUBLE (2) O-RING	4.5" x 10"	3/4"	Blue / Black	5 x 12 (127mm x 305mm)	6	60010559 x 2	93017	NSF CERTIFIED
36053	HOUSING, P-H-PR-10BV-1	PRESSURE RELIEF, DOUBLE (2) O-RING	4.5" x 10"	1"	Blue / Black	7 x 14 (178mm x 356mm)	6	60010559 x 2	93017	NSF CERTIFIED
36112	HOUSING, P-H-PR-20BV-1	PRESSURE RELIEF, DOUBLE (2) O-RING	4.5" x 20"	1"	Blue / Black	7 x 25 (178mm x 635mm)	8	60010559 x 2	93017	NSF CERTIFIED
36114	HOUSING, P-H-PR-20BV-1.5	PRESSURE RELIEF, DOUBLE (2) O-RING	4.5" x 20"	1.5"	Blue / Black	7 x 25 (178mm x 635mm)	8	60010559 x 2	93017	NR
36116	HOUSING, P-H-PR-20BV-3/4	PRESSURE RELIEF, DOUBLE (2) O-RING	4.5" x 20"	3/4"	Blue / Black	7 x 25 (178mm x 635mm)	8	60010559 x 2	93017	NSF CERTIFIED

WARNING: Do not use on drinking water supplies that are microbiologically unsafe or of unknown quality without first adequately disinfecting the water. Protect against freezing to prevent cracking of the filter and water leakage.

NOTE: All dimensions and micron ratings are nominal. The manufacturer reserves the right to make product improvements which may deviate from the specifications and descriptions stated herein, without obligation to change previously manufactured products or to note the change. Do not subject to freezing temperatures.

Your Local Water Specialist

AQUA FLO®

A Division of

