



Specific Features: _____



◆ Your Delta Faucet hand shower incorporates a backflow protection system that has been tested to be in compliance with ASME A112.18.3, ASME A112.18.1/CSA B125.1. It incorporates two certified check valves in series, which operate independently and are integral, non-serviceable parts of the wand assembly.



- **Compel® Bath Collection**
- **Single Handle Roman Tub Faucet with Hand Shower**
- **Three Hole Installation**
- **Rough-In Kit Must Also be Ordered to Complete Installation**

- Hand Shower maximum flow rate 1.75 gpm @ 80 psi, 6.6 L/min @ 550 kPa
- Trim only for single handle Roman Tub Faucet with Hand Shower
- Temperature only controlled with handle
- Hot/cold indicator
- Rough-in Kit must be ordered to complete installation:
 - R3707, R3707-MF and R3707-PX for flexible rough-in.
 - R3716, R3716-MF and R3716-PX for fixed rough-in.

There are separate specification sheets on each rough-in kit, if more detail is required.

- Hand Shower includes double check valves for backflow prevention

▪ **Rough-in must be installed so handle is on the left of the spout with the spout facing forward. Refer to M&I for more details. Spacing between hand shower and spout could be 5" - 8" (127 mm - 203 mm).**

- Lifetime limited warranty on parts (other than electronic parts and batteries) and finishes: or, for commercial users, for 5 years from date of purchase.
- 5 year limited warranty on electronic parts (other than batteries); or, for commercial users, for 1 year from the date of purchase. No warranty is provided on batteries.



55 E. 111th Street, Indianapolis, Indiana 46280
350 South Edgeware Road, St. Thomas, ON N5P 4L1
© 2018 Masco Corporation of Indiana