





SYMMONS Temptrol®

Location:




262XBODY & 162XBODY PRESSURE BALANCING SHOWER & TUB/ SHOWER VALVE BODY SPECIFICATION SUBMITTAL



262XBODY



162XBODY

Model Numbers	Feature Highlights
<input checked="" type="checkbox"/> 262XBODY Pressure Balancing tub/shower valve body with service stops <input type="checkbox"/> 162XBODY Pressure Balancing tub/shower valve body with pressure testing cap and service stops	<ul style="list-style-type: none">• Brass, bronze and stainless steel construction• Pressure balancing mixing valve to maintain safe shower temperature• Adjustable stop screw to limit handle rotation• Integral service stops allow water shut-off for valve servicing• 4 port valve body in common plane• Inlets: 1/2" IPS and 1/2" sweat• Outlets: 1/2" IPS and 1/2" sweat• Accommodates back-to-back installations when using reverse seat• Accommodates thin wall installations• Stringer mounts included
Options/ Modifications	Warranty
<input type="checkbox"/> RV Reverse seat for back-to-back installations <input type="checkbox"/> BR Temptrol Rapid Install™ Bracket <input checked="" type="checkbox"/> CHKS Integral check stops for use in installations where a positive shut-off device is used downstream of valve <input type="checkbox"/> CP CPVC fittings <input type="checkbox"/> P1 PEX crimp fittings <input type="checkbox"/> P2 PEX expansion fittings <input type="checkbox"/> P3 ProPress fittings	<p>Limited Lifetime - to the original end purchaser in consumer/residential installations.</p> <p>10 Years - for commercial/industrial installations. Refer to www.symmons.com/warranty for complete warranty information.</p> 
Compliance	<ul style="list-style-type: none">• ASME A112.18.1/CSA B125.1• ASSE 1016• Buy American Act Compliant  

SKU Builder

Series	Reverse Seat	Check Stops	Rapid Install	Fittings	BODY	Final SKU
262X	RV		BR	P1	BODY	262XRVBPR1BODY
262X		CHKS	BR		BODY	262CHKSBRBODY

Architectural/ Engineering Specification

Symmons _____ PRESSURE BALANCING SHOWER & TUB/ SHOWER VALVE BODY. Includes Brass, bronze, and stainless steel construction, pressure balancing mixing valve to maintain safe shower temperature, adjustable stop screw to control maximum hot water temperature to valve, integral service stops allow water shut-off for valve servicing, 4 port valve body in common plane, inlets: 1/2" IPS and 1/2" sweat, outlets: 1/2" IPS and 1/2" sweat, accommodates back-to-back installations when using reverse seats, accommodates thin wall installations, stringer mounts included. 10 Year Commercial Warranty. ASME A112.18.1/CSA B125.1, ASSE 1016, and Buy American Act compliant. Available options: "RV - Reverse seat for back-to-back installations", "BR - Temptrol Rapid Install™ Bracket", "CHKS - Integral check stops for use in installations where a positive shut-off device is used downstream of valve", "CP - CPVC fittings", "P1 - PEX crimp fittings", "P2 - PEX expansion fittings", and "P3 - ProPress fittings".



262XBODY & 162XBODY

Dimensions

