KOHLER

Wellworth®

Two-piece round-front toilet, 1.28 gpf K-3997

Features

- Two-piece design
- Round-front bowl offers an ideal solution for smaller bathrooms and powder rooms
- 1.28 gpf (4.8 lpf)
- Left-hand Polished Chrome trip lever
- Combination consists of the K-4467 tank and the K-4197 bowl
- Coordinates with other products in the Wellworth collection
- KOHLERs canister flush valve harnesses the natural force of gravity and optimizes flushing performance
- Class Five® canister optimizes the flow out of the tank, harnessing gravity and the natural powerful reducing cascade of water to increase the power and effectiveness of the flush
- Eligible for consumer rebates in some municipalities
- Supply line and Wax Ring not included, but required for installation. Recommended Wax Ring, and Connector Hose part numbers listed below
- 2-1/8" (54 mm) fully glazed trapway

Installation

- Standard 12" (305 mm) rough-in
- Three-bolt quick-connect installation
- Seat and supply line sold separately

Recommended Products/Accessories

K-5589 Purefresh® Deodorizing round-front toilet seat K-76923 PureWash® M250 Quiet-Close™ round-front toilet seat with antimicrobial agent K-5420 Low-Profile Bolt Caps K-9379 Trip Lever 1023457 Wax Ring/Hardware Kit 1265114 Connector Hose K-23726 Drain treatment

Included Components

K-4197 Round-front toilet bowl K-4467 Toilet tank, 1.28 gpf





Codes/Standards ASME A112.19.2/CSA B45.1 DOE - Energy Policy Act 1992 EPA WaterSense® IAPMO Certification

KOHLER® Toilets and Seats Limited Warrantv

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.


Color Code Description



Biscuit


7 Black Black™







Wellworth® Two-piece round-front toilet, 1.28 gpf K-3997



Technical Information

All product dimensions are nominal. Toilet type: Floor-mount Waste Outlet: Floor Round-front Bowl shape: Flush type: **Class Five** Trap passageway: 2-1/8" (54 mm) Water surface size: 10-1/2" x 7-3/4" (267 mm x 197 mm) Rim to water 5-1/4" (133 mm) surface: Rough-in: 12" (305 mm) Seat-mounting 5-1/2" (140 mm) holes:

Notes

Install this product according to the installation instructions.

For back-to-back toilet installations: Use only a 45° double wye fitting.

