







see what Delta can do

BATHROOM FAUCETS

- Modern Cylindrical™
- Single Handle Deck Mount

STANDARD SPECIFICATIONS:

- Max flow rate 1.2 gpm @ 60 psi, 4.5 L/min @ 414 kPa (Aerated pressure compensating)
- Optional Water-efficient outlet RP79322 for 1.0gpm @ 60 psi, 3.8L/min @ 414 kPa (aerated pressure compensating)
- Optional Water-efficient outlet RP79323 for 0.5gpm @ 60 psi, 1.9L/min @ 414 kPa (cascade pressure compensating)
- One or three hole mount (Optional RP78359 3 hole Escutcheon, not included)
- 2 1/4" max. deck thickness
- Ceramic cartridge with high temperature rotational stop
- Red/blue indicator markings
- Metal lever handle
- Solid brass body
- 14" long flexible supply lines with 3/8" supply fittings
- Rigid Spout with 5 ¼" length reach
- Models have 50/50 pop-up type fitting with plated flange and stopper

WARRANTY

- Parts and Finish Lifetime limited warranty; or for commercial purchasers, 10 years for multi-family residential (apartments and condominiums) and 5 years for all other commercial uses, in each case from the date of purchase.
- Electronic Parts and Batteries (if applicable) 5 years from the date of purchase; or for commercial purchasers, 1 year from the date of purchase. No warranty is provided on batteries









COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1
- EPA WaterSense®- Applies to 560LF-▲PP with 1.2 gpm @ 60 psi, 4.5 L/min @ 414 kPa outlet.
- Verified compliant with 0.25% weighted average Pb content regulations
- Indicates compliance to ICC/ANSI A117.1