

Submitted Model No.:

Specific Features:

Min. 2 1/2" (64 mm) Clearance To Back Splash 5 3/4" 5 13/16" (148 mm) (146 mm) 8 9/16" (218 mm) 7 3/4" (197 mm) 2 3/16" 56 mm) 2 11/16" (68 mm) Max. 3 5/16" (84 mm) 1 7/8" (48 mm) 1 3/8" (35 mm) Hole Size Thickness 15 3/8" (391 mm) 1 5/8" (41 mm) 2 1/8" (54 mm) to 2 3/8" (60 mm) 1/2" I.P.S. 3 3/8" (86 mm) ___ 1 3/8" (35 mm) Dia. 4 5/8" (118 mm) 1 1/4" (32 mm) Dia.

▲ Designate Proper Finish Suffix

Brizo Kitchen & Bath Company reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.brizo.com for finish options and product availability.

BRIZO

LAVATORY **FAUCETS**

- Loki[®] Bath Collection
- Two Handle Deck Mount
- Single Hole Mount
- Swivel Spout

STANDARD SPECIFICATIONS:

- Two handle lavatory faucet for concealed mounting on one hole applications.
- 5 13/16" (148 mm) long spout.
- Recommended 1 3/8" hole size.
- Spout swivels 120°.
- Model has metal drain with pop-up type fitting with plated flange and stopper.
- Accomodates up to 3 5/16" deck thickness.
- Control mechanism shall be of the rotating ceramic cylinder type.
- Handles slide on and off.
- Maximum 1.50 gpm @ 60 psi, 5.7 L/min @ 414 kPa

WARRANTY

- Lifetime limited warranty on parts (other than electronic parts and batteries) and finishes: or, for commercial users, for 5 years from date of purchase.
- 5 year limited warranty on electronic parts (other than batteries); or, for commercial users, for 1 year from the date of purchase. No warranty is provided on batteries.





COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1
- ASME A112.18.2 / CSA B125.2
- Indicates compliance to ICC/ANSI A117.1
- EPA WaterSense®
- Verified compliant with .25% weighted average Pb content regulations.

Brizo Kitchen & Bath Company Indianapolis, Indiana 46280 A Division of Masco Corporation of Indiana © 2015 Brizo Kitchen & Bath Company