


# BRIZO®






## LAVATORY FAUCET

- Tresa® Collection
- Two Handle Widespread Bridge



Submitted Model No.: \_\_\_\_\_

Specific Features: \_\_\_\_\_



▲ Designate proper finish suffix

### STANDARD SPECIFICATIONS:

- Max flow rate: 1.50 GPM @ 60 PSI, 5.68 L/Min @ 414 kPa
- Max flow rate (ECO models only): 1.20 GPM @ 60 PSI, 4.54 L/Min @ 414 kPa
- Two or three hole mount
- Ceramic cartridge
- Hot and cold stems are interchangeable
- 1/4 turn handle stops
- Optional (not included) push button drain assembly (RP72414 or RP72413)
- Optional (not included) grid strainer drain available with overflow (RP72412) or without (RP72411)
- Solid brass with one-piece cast brass waterway
- Third hole cover included

### WARRANTY:

- Lifetime limited warranty on parts (other than electronic parts and batteries) and finishes: or, for commercial users, for 5 years from date of purchase.
- 5 year limited warranty on electronic parts (other than batteries); or, for commercial users, for 1 year from the date of purchase. No warranty is provided on batteries.



### COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1
- ASME A112.18.2 / CSA B125.2
- ♿ Indicates compliance to ICC/ANSI A117.1
- EPA WaterSense®
- Verified compliant with 0.25% weighted average Pb content regulations