# **450-SERIES** Submersible Sump Pumps

Liberty Pumps<sup>®</sup>

A Family and Employee Owned Company

## 1/2 hp 1-1/2" Discharge 3/8" Solids handling

#### **Features**

- Vortex impeller permits passage of solids without clogging
- Polypropylene and powder coated aluminum construction
- Stainless-steel rotor shaft
- Non-corrosive stainless-steel fasteners
- Oil-filled, hermetically sealed motors with thermal overload protection
- Permanently lubricated upper and lower bearings
- Quick-connect 10' standard power cord allows replacement of cord in seconds without breaking seals to motor. (25' length optional)

Deep finned powder coated aluminum motor housing provides over 200% more cooling capacity than cast iron housings!



- 450 Manual
- **451** Mercury-free wide-angle float switch, integrally wired, with Quick-connect feature
- **453** Mercury-free wide-angle float switch, with series plug
- 457 VMF, Vertical Magnetic Float switch

Model 457 VMF





## 450-Series

#### Impeller

Vortex style high temp engineered thermoplastic

#### Finishing

Powder coat

#### Max Fluid Temperature

140°F (60°C) Intermittent 104°F (40°C) Continuous duty

#### Power Cord Type

SJTW Quick-connect 10' standard (25' length optional). For 25' optional cord length, add a "-2" suffix to model number. Example: 451-2 for Model 451 with 25' cord

#### Motor Housing

Aluminum

#### Shaft

Stainless

#### Hardware

Stainless

#### Mechanical Shaft Seal

Engineered double lip seal with stainless-steel springs

### Bearings

Permanently lubricated upper and lower ball bearings

#### **Motor Specifications**


1/2hp 115V 7.3A Oil-filled; thermally protected

#### **Dimensional Data**

Weight: 12.5 lbs Height: 12.5" Major Width: 9.6" Minimum Sump Diameter: 14" (10" on Model 457)


#### Performance Curve

60 Hz 3450 RPM




#### Sump Models






**Effluent Models** 

Quick-connect wide-angle float switch



Model 453 Wide-angle float switch with series (piggyback) plug allows for manual operation of pump



Model 457 VMF VMF, magnetically operated vertical float switch - operates in a 10" diameter sump

Liberty Pumps - 7000 Apple Tree Avenue - Bergen, New York 14416 Phone 800-543-2550 - Fax 585-494-1839 - www.LibertyPumps.com

Specifications subject to change without notice.

Copyright © Liberty Pumps, Inc. 2022 All rights reserved. LLIT004800-R11/22