



Submitted Model No.: \_\_\_\_\_

**Specific Features:** 

## (51mm) 5 1/4" (133mm) 36" 7 3/4 (910mm) (197mm) 6 1/2" OPTIONAL 165mm) FACE OF PLASTERGUARD SHOULD BE FLUSH WITH FINISHED WALL LINE 7 7/8" (200mm) 8' HOT & COLD INLETS (203mm) Min. 18" FINISHED WALL (457mm) 36" Max. 1/2" FIP (910mm) OPTIONAL 5" -1 3/4" to 2 1/2" (127mm) (44mm to 66mm) TO FLOOR







# TUB & SHOWER FAUCET TRIM

- Modern Angular
- Valve Only Trim (T14067-PP)
- Shower Only Trim (T14267-PP)
- Tub/Shower Trim (T14467-PP)
- Shower Only Trim Less Showerhead (T14267-PP-LHD)
- Tub/Shower Trim Less Showerhead (T14467-PP-LHD)

#### **STANDARD SPECIFICATIONS:**

- Single handle pressure balanced tub and shower mixing valve.
- Maintains a balanced pressure of hot and cold water even when a valve is turned on or off elsewhere in the system.
- For use with MultiChoice® Universal rough valve body
  NOT INCLUDED AND MUST BE ORDERED
  SEPARATELY (R10000 Series).
- 1/2" FIP threaded metal tub spout with pull-up diverter.
- Back-to-back installation capability.
- Field adjustable means to limit handle rotation into hot water zone
- Temperature only controlled with handle.
- All parts replaceable from the front of the valve.
- "LHD" indicates less showerhead models.
- Maximum flow rate of spout: 6.8 gpm @ 60 psi (25.7 L/min @ 414 kPa) or full flow.
- Maximum flow rate of showerhead: 1.75 gpm @ 80 psi (6.6 L/min @ 552 kPa).

### **WARRANTY**

- Lifetime Faucet and Finish Limited Warranty to the original consumer purchaser to be free from defects in material and workmanship.
- 5 Year Limited Warranty for usage in all industrial, commercial and business applications.



## **COMPLIES WITH:**

- ASME A112.18.1 / CSA B125.1
- ASSE 1016-P

Indicates ADA compliance to ICC/ANSI A117.1 – Valve control only

