




Dimensions



* Distance from bottom of sink to center line of disposer outlet. Add1/2" when stainless steel sinks are used.

** Length of tailpipe from center line of disposer outlet to end of tailpipe. NOTE: Plumb waste line to prevent standing water in disposer motor housing.

Job Specifications

STANDARD SERIES

Badger[®] 1

Submittal Sheet

This model offers the following features and benefits:

- Lift & Latch[™] technology for easier sink connection
- 1/3 Horsepower Heavy Duty Motor (Quiet Dura-Drive[®] Induction Motor)
- We Come To You® 1-Year In-Home Limited Warranty
- Rugged Galvanized Steel Construction (For Disposer Durability)
- Space-Saving Compact Design
- Available with or without a factory installed power cord.

Sample Specification

Food Waste Disposer(s) shall be InSinkErator Badger® 1, continuous feed, with 1/3 H.P. motor, galvanized steel grinding elements with two stainless steel 360° swivel lugs. Exclusive self-service wrench.

Available with or without a factory installed power cord.

Warranty:

1-Year parts and in-home service.

* The complete InSinkErator warranty is included in the Care & Use Booklet packed with each unit.



Food waste is roughly 80% water. By using your disposal regularly, you can help divert food waste from landfills and reduce greenhouse gas emissions. Make sustainability a family affair by using your disposal. After all, the smallest changes can make the biggest impact.





The Emerson logo is a trademark and service mark of Emerson Electric Co. The mounting collar configuration is a trademark of Emerson Electric Co.

InSinkErator may make improvements and/or changes in the specifications at any time, in its sole discretion, without notice or obligation and further reserves the right to change or discontinue models.

1-800-558-5700 www.insinkerator.com

On/Off Control Wall Switch Motor Single Phase

Type of Feed

Specifications

Continuous

| HP | 1/3 |
|---------------------------------|---|
| Volts | 120 |
| HZ | 60 |
| RPM | 1725 |
| Amp. (Avg. Load) | 5.6 |
| Time Rating | Intermittent |
| Lubrication | Permanently Lubricated Upper & Lower Bearings |
| Shipping Weight (Approx.) | 12 lbs. 10 oz. (without cord) 12 lbs. 14 oz. (with cord) |
| Unit Finish | Condor Grey |
| Overall Height | 11-1/2" |
| Grind Chamber Capacity | 26 oz. |
| Motor Protection | Manual Reset Overload |
| Average Water Usage | Approx. 1 Gallon per Person Per Day |
| Average Electrical Usage | 3-4 KWh per Year |
| Drain Connection | 1-1/2" Cushioned Slip Joint |
| Dishwasher Drain Connection | Yes |
| Factory Installed Power Cord | Available with or without |