


Submitted Model No.:_

Specific Features:



Designate Proper Finish Suffix

Delta reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.deltafaucet.com for finish options and product availability.



see what Delta can do

FLOOR MOUNT TUB FILLER

■ Stryke[™] Bath Collection

FEATURES:

- H₂Okinetic[®] Technology
- Multichoice[®] high flow non pressure balance cartridge

STANDARD SPECIFICATIONS:

- Hand shower maximum flow rate 1.75 gpm @ 80 psi, 6.6 L/min @ 550 kPa Hot and cold indicators
- 60"-82" (1524 mm 2083 mm) stretchable hose with metal fittings
- Auto resetting diverter
- Pivot hand shower holder
- Rough-In R4700-FL or R4700-FLWS, required for installation
- Dual integral check valve on hand shower

WARRANTY

- Lifetime limited warranty on parts (other than electronic parts and batteries) and finishes: or, for commercial users, for 5 years from date of purchase.
- 5 year limited warranty on electronic parts (other than batteries); or, for commercial users, for 1 year from the date of purchase. No warranty is provided on batteries.



COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1 Indicates compliance to ICC/ANSI A117.1 - Valve control only
- EPA WaterSense[®] Hand shower only (RP100396▲)

Delta Faucet Company

55 E. 111th Street, Indianapolis, IN 46280 350 South Edgeware Road, St. Thomas, ON N5P 4L1 © 2018 Delta Faucet Company