

*There is more than 1 version of this model.
Page down to identify the version you have.*

DESCRIPTION

- One piece, cast brass construction above-deck with various finishes identified by suffix
- Transitional style matches M•Power™ soap dispenser (model 8558)
- 4" centerset
- Vandal resistant aerator
- Flexible stainless steel supply line
- Vandal resistant below-deck box with included mounting hardware

OPERATION

- "Touch free" operation for improved hygiene
- Adjustable sensor activation distance from 3" to 12" (default 5-1/2")
- Vandal Mode: 30 second time-out feature
- Maintenance / Cleaning Mode: Allows for a 30 second deactivation for maintenance or cleaning
- Sentinel Flow: Eliminates stagnant water supply lines every 24 hours (factory setting = off)
- Metering Mode Feature: Adjustable run time from 10 to 180 seconds (factory setting = off)
- Battery 4 (AA) with AC compatibility
 - For AC connection: Transformer 104630 required for up to 8 devices, and 182538 connector for each device
- Battery level indicator with low battery warning light
- Battery life: Up to 8 years*
- In-line filter included

FLOW

- 0.5 gpm (1.9 L/min) vandal-resistant multi-stream laminar flow

STANDARDS

- Third party certified to meet ASME A112.18.1/CSA B-125.1, and all applicable requirements referenced therein including NSF 61/9 & 372
- Complies with California Proposition 65 and with the Federal Safe Drinking Water Act
- Meets the current requirements of the Buy American Act (BAA)
- ADA  compliant

WARRANTY


- Warranted for 5 years against material or manufacturer defects
- * Typical alkaline battery life at 150 uses per day



M•Power™ Electronic Faucet Below-Deck Transitional Style

Models: CA8301 Series

NOTE: DESIGNED TO BE INSTALLED
THROUGH 3 HOLES, 1" MIN. DIA.
& 2" ON CENTER



Optional

**Adjustable Temperature
Thermostatic Mixing Valve**
104451

- Minimum flow rate of .35gpm
- ASSE 1070 & CSA B-125.1 certified

For models manufactured before July 2016.

FAUCET DESCRIPTION

- Solid brass body with chrome plated finish
- Elegant styling
- 4" centerset

OPERATION

- Adjustable infrared sensor (range, turn off delay and obstruction delay)
- Temperature controlled by mixing valve or mixing tee (optional)
- Battery powered (AC optional)

FLOW

- Supplied with vandal resistant 0.5 gpm (1.9 L/min) aerator (with key)

VALVES


- In-line filter included
- Slow close solenoid valve

STANDARDS

- Third party certified to ASME A112.18.1/CSA B-125.1 and all applicable specifications referenced therein
- Contains no more than 0.25% weighted average lead content
- Complies with California Proposition 65 and with the Federal Safe Drinking Water Act
- ADA  for lever handles

WARRANTY

- Warranted for 5 years against material or manufacturer defects



M•Power™ Deck-Mount (4" Center), Non-Mixing, Battery Powered Electronic Faucet

Models: CA8301 series

NOTE: DESIGNED TO BE INSTALLED
THROUGH 3 HOLES 1" MIN. DIA. 2"
ON CENTER

