Rapid SL Wall Carrier for Toilet MODEL # 38749002





GROHE CANADA, INC.| 5900 Avebury Road, Mississauga, Ontario, Canada L5R 3M3 Phone: 905-271-2929 | Fax: 905-271-9494 | info@grohe.ca





Product Description: Rapid SL Wall Carrier for Toilet


Standard Specification: • Flushing cistern GD 2 1.13 m installation height for on-the-wall installations or studded walls powder coated steel frame, self-supporting for dry-cladding, completely pre-assembled with fixed connections quick adjustment, lockable • Fixing material **TÜV** approved 2 WC fixing bolts fixing device for ceramic distance of fixing bolts 180/230 mm inlet and outlet connecting set flushing cistern GD 2, 6 - 9 I pneumatic discharge valve offering 3 modes of operation: dual flush or start/stop or single flush water supply from left/right or back low noise (group I acc. to German Noise Specification) insulated against condensation 1/2" water supply connection including integrated angle valve and push fit flexible hose union • No tools required for the installation of the inspection shaft

- incl. protection during construction phase
- For vertical or horizontal use
- without accessories for-on-the-wall installation
- For mounting of small flush plates please order revision shaft 40 911 000 (sold separately)

Applicable Codes & Standards:

- Energy Policy Act of 1992
- ASME A112.18.1/CSA B125.1

Color: 38749002



GROHE CANADA, INC.| 5900 Avebury Road, Mississauga, Ontario, Canada L5R 3M3 Phone: 905-271-2929 | Fax: 905-271-9494 | info@grohe.ca