

Submitted Model No.:

Specific Features:

12 1/2" to 22 1/2" (318 mm to 572 mm) 6" to 16" (152 mm to 406 mm) Centers Min. 2 1/2" (64 mm) Clearance To Back Splash 5 9/16" (141 mm) 2 3/8" (60 mm) 3 1/4" (83 mm) 3 3/16" (81 mm) 7 27/32" (199 mm) 4 7/8' (124 mm) _ 2 3/8" (60 mm) 3x 1 1/8" to 1 1/2" (29 mm to 38 mm) Hole Size 7 3/4" (196 mm) 1 5/8" (42 mm) to 2 3/8" (61 mm) 2 1/8" (54 mm) Flexible Hose Connection — 3/8" O.D. — Copper Tubing do. (76 mm) Max. Deck Thickness 1/2" IPS 3 3/8" (86 mm) _3/8" (35 mm) Dia. 4 5/8" (118 mm) -1 1/4" (32 mm) Dia.

▲ Designate Proper Finish Suffix

BRIZO

LAVATORY FAUCETS

- Virage[®] Collection
 Two Handle Widespread Deck Mount

STANDARD SPECIFICATIONS:

- Maximum 1.5 gpm @ 60 PSI, 5.7 L/Min @ 414 kPa
- Three hole mount
- Control mechanism shall be of the rotating ceramic cylinder type with 90° (1/4 turn) rotation
- Metal drain with pop-up type fitting with plated flange and stopper

WARRANTY

- Lifetime limited warranty on parts (other than electronic parts and batteries) and finishes: or, for commercial users, for 5 years from date of purchase.
- 5 year limited warranty on electronic parts (other than batteries); or, for commercial users, for 1 year from the date of purchase. No warranty is provided on batteries.



COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1ASME A112.18.2 / CSA B125.2
- Indicates compliance to ICC/ANSI A117.1
- EPA WaterSense®
- "LF" models verified compliant with .25% weighted average Pb content regulations.