



Specific Features:



3 1/8"
(79 mm)

8"-16"
(203-406 mm)
Centers (Flexible)

2x 2 1/2"
(64 mm)

← 2 1/2"
(64 mm)

5 9/16"
(141 mm)

10"
(254 mm)

6 5/16"
(160 mm)

4" (32 mm)

← 2 3/4
(70 mm)

59" HS Hose



see what Delta can do SM

ROMAN TUB/WHIRLPOOL FAUCET TRIM

- Galeon™ Bath Collection
- Three Hole Installation (T2771 Series)
- Four Hole Installation (T4771 Series)

FEATURES:

- Lumicoat™ Finish (-PR models only)
- Lumicoat™ Finishes easily wipe clean without cleaners and chemicals on the products most commonly touched areas

STANDARD SPECIFICATIONS:

- Temperature and volume controlled with handles
- Rough-In kit must also be ordered to complete installation
 - R4707 for four hole
 - R2700 or R2707 for three hole
 - RP23601 for three hole 10" fixed installation
 There are separate specification sheets on each rough-in kit if more details are required.
- Hand shower includes certified double check valves for backflow prevention (T4771)
- Hand shower max flow rate 1.75 gpm @ 80 psi, 6.6 L/min @ 550 kPa
- Hot/cold indicators

WARRANTY

- Parts and Finish - Lifetime limited warranty; or for commercial purchasers, 10 years for multi-family residential (apartments and condominiums) and 5 years for all other commercial uses, in each case from the date of purchase.
- Electronic Parts and Batteries (if applicable) - 5 years from the date of purchase; or for commercial purchasers, 1 year from the date of purchase. No warranty is provided on batteries.

**COMPLIES WITH:**

- ASME A112.18.1 / CSA B125.1
-  Indicates compliance to
 ICC/ANSI A117.1 - Valve control only
- EPA WaterSense® - Applies to T4771▲ only