39675000 Left-Hand Trip Lever
39676000 Right-Hand Trip Lever
ESSENCE
TWO-PIECE ELONGATED SINGLE FLUSH TOILET



STANDARD SPECIFICATION:

- Elongated bowl design
- Made of vitreous china in Alpine White
- 12" (305 mm) rough-in
- Siphon action jetted bowl with smooth-sided, concealed trapway
- ADA Height
- Left and right hand trip lever options available
- High efficiency, low consumption 1.28 gpf/4.8 Lpf
- InfinaBright™ surface coating reduces dirt and bacteria build-up ensuring the surface shines longer
- DreamClean™ Rim scrubs the top to bottom with every flush
- 16-1/2" (419 mm) rim height
- Fully-glazed 2-1/8" (54 mm) trapway
- 3" (76 mm) flush valve
- Includes slow-close telescoping seat
- Color-matched bolt hole covers

COMPONENTS:

39737000 - Elongated Toilet Seat: Slow-Close, Top-mount, Easy Lift Off, Telescoping
39679000 - Tank - Left-Hand: 1.28 gpf 12" rough-in complete with coupling components and tank trim
39680000 - Tank - Right-Hand: 1.28 gpf 12" rough-in complete with coupling components and tank trim
39677000 - ADA Height Elongated Bowl with Seat
39671000 - Tank Cover
49140000 - Plated Trip Lever - Left-Hand in Chrome
49140EN0 - Plated Trip Lever - Left-Hand in Brushed Nickel
49143000 - Plated Trip Lever - Right-Hand in Chrome
49143EN0 - Plated Trip Lever - Right-Hand in Brushed Nickel

APPLICABLE CODES & STANDARDS:

- Complete listing will be available by July 2020

- Watersense
- ADA
- CEC and CALGreen® Compliant

CALGreen® is a registered trademark of California Building Standards Commission.

NOTE: Install this product according to the installation guide. ADA, CSA compliant when installed to the specific requirements of these regulations.

©2020 LIXIL WATER TECHNOLOGY


39675000 Left-Hand Trip Lever
39676000 Right-Hand Trip Lever
ESSENCE
TWO-PIECE ELONGATED
SINGLE FLUSH TOILET

TECHNICAL DATA:

DIMENSIONS:

NOMINAL DIMENSIONS
29-1/2″x 16-9/16″x 31-1/8″
(738 x 420 x 790 mm)

WATER SPOT
7-7/8″ (200 mm) wide
9-1/4″ (235 mm) length
5-1/2″ (140 mm) distance to rim



NOTES:
This toilet is designed to rough-in at a minimum dimension of 12″ (305 mm) from finished wall to C/L of outlet.
Supply not included with fixture and must be ordered separately.
Dimensions shown for location of supply is suggested.

IMPORTANT:
Dimensions of fixtures are nominal and may vary within the range of tolerance established by ANSI Standard A112.19.2.
These measurements are subject to change or cancellation. No responsibility is assumed for use of superseded or voided pages.

©2020 LIXIL WATER TECHNOLOGY