

Kitchen Faucet S-23 Series

Specification Submittal

Feature Highlights

- Single lever kitchen faucet with red & blue indicators on handle
- Handle limit stops
- 8-3/4 inch swing spout with aerator
- Ceramic control components
- Supply has 3/8 inch copper tubing, 8-inch centers
- Metal contruction, polished chrome finish
- 2.2 gpm (8.3 L/min) standard flow rate



Standards / Certifications

ASME A112.18.1/CSA B125.1 NSF/ANSI 61.9, NSF/ANSI 372



- Warranty
- Limited Lifetime to the original end purchaser in consumer installations.
- 5 years for commercial installations

	S-23 s	series	
S-23-2-LP	S-23-2-W	S-23-1	S-23-3
E		E	E C C C C C C C C C C C C C C C C C C C

Ordering Information

Model Numbers

Append appropriate -suffix to model number.

_

S-23 Faucet only

S-23-1 Faucet with swivel spray aerator in place of hose and spray (not available in low flow).

☐ S-23-2 Faucet with hose and spray

☐ S-23-3 Faucet with hose and spray mounted on

escutcheon

Finish Options / Modifications

Append appropriate -suffix to model number.

☐ -STN Satin nickel finish*



Polished chrome (standard finish)

Handle Options / Modifications

Append appropriate -suffix to model number.

- ☐ -LP Loop handle
- -W Lever handle 6 inch (152 mm) chrome only

Other Options

Append appropriate -suffix to model number.

-LST 18 inch copper supply tubing

1

П

-BH 20 inch (508 mm) braided hose supplies (not available with -SM option for S-23-2 and S-23-3 configurations)

-10 10-7/8 inch swing spout with aerator

☐ -IPS 1/2 inch IPS connections

© -0.5 Vandal resistant, 0.5 gpm (1.9 L/min) aerator

☐ 66 -1.5 1.5 gpm (5.7 L/min) aerator

-VP Vandal resistant, 2.2 gpm (8.3 L/min) aerator

□ -VP-1.5 Vandal resistant, 1.5 gpm (5.7 L/min) aerator

□ -NA Non-aerated, 2.2 gpm (8.3 L/min) laminar flow outlet

-SM Single hole mounting (not available with -BH option for S-23-2 and S-23-3 configurations)



