# **KOHLER**<sub>®</sub>

### Corbelle® Tall two-piece elongated toilet with skirted trapway, 1.28 gpf

K-33813

### Features

- Two-piece design
- Elongated bowl offers added room and comfort
- Tall height offers seating 2-1/2" (63.5 mm) higher than Comfort Height<sup>®</sup> for enhanced comfort, ease of sitting and standing, and gracious accessiblity
- 1.28 gpf (4.8 lpf)
- Left-hand Polished Chrome trip lever
- 2-1/8" (54 mm) glazed trapway
- Revolution 360<sup>®</sup> flushing technology generates a forceful swirling motion to keep the bowl clean longer
- Fully skirted trapway simplifies cleaning
- Sanitary guard where bowl and tank meet for ease of cleaning
- Encapsulated bolts prevent rust and corrosion
- Patented ReadyLock<sup>®</sup> installation system, a simple solution for skirted toilets, saves time, hassle, and eliminates the need to drill into the floor for standard 12" (305 mm) rough-in
- CleanCoat<sup>™</sup> surface treatment inhibits the growth of water scale and mineral stains for improved ease of cleaning
- AquaPiston® canister optimizes the flow out of the tank, harnessing gravity and the natural powerful reducing cascade of water to increase the power and effectiveness of the flush

### Installation

- Three-bolt quick-connect installation
- Standard 12" (305 mm) rough-in
- 10" and 14" (254 mm and 356 mm) rough-in kits also available
- Seat and supply line sold separately

### **Recommended Products/Accessories**

K-20120-L Trip Lever

K-4108 PureWash® E750 Elongated bidet toilet seat with remote control

K-27331 Glissade® ReadyLatch® Quiet-Close™ elongated toilet seat

### **Included Components**

K-4143 Toilet tank, 1.28 gpf K-33812 Tall elongated toilet bowl with skirted trapway





C

### **Codes/Standards**

ASME A112.19.2/CSA B45.1 DOE - Energy Policy Act 1992 EPA WaterSense® California Energy Commission (CEC) IAPMO Certification

## KOHLER® Toilets and Seats Limited Warranty

See website for detailed warranty information.

### Available Colors/Finishes

Color tiles intended for reference only.

olor	Code	Description
	0	White
	96	Biscuit
	95	lce™ Grey
	7	Black Black™





Corbelle® Tall two-piece elongated toilet with skirted trapway, 1.28 gpf K-33813

#### For Back-to-Back Toilet Installations 1-1/8" Use a 45° double Do not use a (29 mm) -28-3/4" (730 mm)double sanitary tee. wye fitting. 8-3/4" 16-3/8" Front of Bowl (222 mm) (416 mm) 11-5/16" (287 mm) P F 7/8" 15-7/8" (22 mm) (403 mm) 34-5/16" 2-1/2" (872 mm) (64 mm) 19" 10-9/16" 3/8 NPT (483 mm) (268 mm) þ 6" (152 mm) 10-11/16 (271 mm) € Of Outlet 12" (305 mm) 8" (203 mm)

### **Technical Information**

All product dimensions are nominal.			
Toilet type:	Floor-mount		
Waste Outlet:	Floor		
Bowl shape:	Elongated		
Flush type:	AquaPiston, Revolution 360		
Trap passageway:	2-1/8" (54 mm)		
Water surface size:	9-3/4" x 7-1/4" (248 mm x 184 mm)		
Rim to water surface:	6-1/4" (159 mm)		
Rough-in:	12" (305 mm)		

### **Fixture Supply Requirements**

Min static pressure:	15 psi (103.4 kPa)
Max static pressure:	80 psi (551.6 kPa)

### Notes

Install this product according to the installation instructions.

