

Submitted Model No.:

Specific Features: Min. 2 1/2" (64 mm) Clearance to Back Splash 2 3/4" Recommended (70 mm) 6" to 16" 5 1/4" (152 mm to 406 mm) (133 mm) Centers 8 3/16" (208mm) 5 7/8" (150 mm) 3 1/16" (79 mm) 1 1/8" 1 3/16" (29mm) (30 mm) 6 15/16" Max. Deck 3 X 1 1/8"~1 1/2" (177mm) ā (29~38 mm) Thickness Hole Size -1/2"-14NPSM 5/8" (42 mm) 2 3/8" (61 mm) 8 5/8" (220 mm) 1 1/4" (32 mm) Dia.

▲ Designate proper finish suffix

Delta reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.deltafaucet.com for finish options and product availability.



see what Delta can do

BATHROOM FAUCET

- Nicoli® Collection
- Two Handle Widespread, Deck Mount

STANDARD SPECIFICATIONS:

- Max. flow rate 1.2 gpm @ 60 psi, 4.5 L/min @ 414 kPa
- Solid brass end valves and spout body
- Three hole mount
- Hot and cold stems are interchangeable
- 1/4 turn handle stops
- 1/4" O.D. coper supply lines
- Control mechanism is a rotating cylinder type with stainless steel plate and 90° rotation, with replaceable non-metallic seats
- Models have drain with pop-up type fitting with plated flange and stopper

WARRANTY

- Parts and Finish Lifetime limited warranty; or for commercial purchasers, 10 years for multi-family residential (apartments and condominiums) and 5 years for all other commercial uses, in each case from the date of purchase.
- Electronic Parts and Batteries (if applicable) 5 years from the date of purchase; or for commercial purchasers, 1 year from the date of purchase. No warranty is provided on batteries.



COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1
- ASME A112.18.2 / CSA B125.2

Indicates compliance to ICC / ANSI A1 17.1 - Valve control only

■ EPA WaterSense®

Delta Faucet Company 55 E. 111th Street, Indianapolis, IN 46280 350 South Edgeware Road, St. Thomas, ON N5P 4L1 © 2020 Delta Faucet Company