

Mini™ & Mini™-E Handwashing Sink Sizing Guide

This guide shows possible point-of-use fixture or fixtures for use with each Mini™ or Mini™-E. It is not intended for whole house sizing. Use actual achievable flow rates to determine if a particular model and size will deliver the temperature and flow rate required for the installed fixture.

FIXTURES & FLOW RATES

SHOWING POSSIBLE
MODEL SUITABILITY

TEMP. FOR MAX.
FLOW RATE
CALCULATION

SINGLE LAV SINK

(Range 0.5-1.5)




90°F



MULTIPLE SINKS

Number varies



Recommendations are correct if unit is installed with 240 V service. Increase one model size if unit will be installed with 208 V service.

Call Stiebel Eltron at 800.582.8423 if you have any sizing questions, or if you have an out-of-the-ordinary situation. Stiebel Eltron service representatives can make recommendations on sizing, or provide assistance with our water heaters, to both homeowners and professional installers.

42°F

52°F

62°F

72°F

Mini™/Mini™-E 2-1

Min. activation 0.21 GPM | Internally restricted to 0.32 / 0.40 GPM

MAX. FLOW RATE

0.26 GPM

0.32 GPM

0.32 / 0.40 GPM

0.32 / 0.40 GPM

POSSIBLE FIXTURE TYPES



Mini™/Mini™-E 2.5-1

Min. activation 0.40 / 0.30 GPM

MAX. FLOW RATE

0.34 GPM

0.43 GPM

0.59 GPM

0.91 GPM

POSSIBLE FIXTURE TYPES



Mini-E 2.5-1 only



Mini™/Mini™-E 3-1

Min. activation 0.40 / 0.30 GPM

MAX. FLOW RATE

0.43 GPM

0.54 GPM

0.73 GPM

1.14 GPM

POSSIBLE FIXTURE TYPES



Mini™/Mini™-E 3.5-1 OR Mini™/Mini™-E 4-2

Min. activation 0.40 / 0.30 GPM

MAX. FLOW RATE

0.50 GPM

0.63 GPM

0.85 GPM

1.33 GPM

POSSIBLE FIXTURE TYPES



Mini™/Mini™-E 6-2

Min. activation 0.77 / 0.30 GPM

MAX. FLOW RATE

0.81 GPM

1.02 GPM

1.39 GPM

2.16 GPM

POSSIBLE FIXTURE TYPES



Mini-E 6-2
1 or 2 sinks

Scroll for temp rise charts. ↓

Mini™ & Mini™-E Handwashing Sink Sizing Guide

