# ) MOEN

## Buy it for looks. Buy it for life.®

## FAUCET DESCRIPTION

- Reflex<sup>™</sup> pulldown system offers smooth operation, easy movement and secure docking
- Metal construction with various finishes identified by suffix
- Duralock<sup>™</sup> quick connect system
- Power Boost<sup>™</sup> Technology provides boosted water performance with the push of a button
- Flexible supply lines with 3/8" compression fittings
- High arc spout provides height and reach to fill or clean large pots while pull out wand provides the maneuverability for cleaning or rinsing


### 360° rotating spout OPERATION

- Lever style handle
- Right hand mount only
- Temperature controlled by 100° arc of handle travel Operates with less than 5 lbs. of force
- Operates in stream or spray mode in the pullout or retracted position
- FLOW
- Standard flow is limited to 1.5 gpm (5.7 L/min) at 60 psi
- Power Boost™ Button activates Boosted Stream and Boosted Spray
- CARTRIDGE
- 1255<sup>™</sup> Duralast<sup>™</sup> cartridge for Single-Handle Faucets
- STANDARDS Third party certified to IAPMO Green, ASME A112.18.1/CSA B125.1 and all applicable requirements referenced therein
- Certified to NSF 61/9 & 372
- Meets CalGreen and Georgia SB370 requirements
- Complies with California Proposition 65 and with the Federal Safe Drinking Water Act
- The backflow protection system in the device consists of two independently operating check valves, a primary and a secondary which prevent backflow
- ADA (5. for lever handle

## WARRANTY

- Lifetime limited warranty against leaks, drips and finish defects to the original homeowner
- 10 year limited warranty when used in a multifamily installation
- 5 year limited warranty when used in a commercial installation
- Visit www.moen.com/support for complete details and limitations

## Specifications



## **HADLEY**<sup>™</sup> Single Handle High Arc **Pulldown Kitchen Faucet**

## Models: 87245 series

**NOTE:** THIS FAUCET IS DESIGNED TO BE INSTALLED THROUGH 1, 2, 3 AND 4

HOLES, 1-1/2" (38mm) MIN. DIA.

(1 HOLE FOR SOAP DISPENSER)



7-7/8"

