

Submitted Model No.:

Specific Features:

62543LF▲, 62553LF▲, 62563LF▲ 62544LF▲, 62554LF▲, 62564LF▲ 13 3/4" (349 mm) 14" (356 mm) € (203 mm) → € (203 mm) → Recommended Minimum of 4 1/4" (108 mm) Min. 2 1/2" (64 mm) Clearance to Back Splash 7 1/16' 5 1/2" (138 mm) (178 mm) 1 1/4" to-1 1/2" (32 mm to 38 mm) Hole Size (51 mm) 3" (76 mm) Max. Deck Thickness 9" (229 mm) 1/2"-14 NPSM Female Fitting 62543LF▲ & 62544LF▲ 62553LF▲ & 62554LF▲ 62563LF▲ & 62564LF▲ Min. 2 1/2" (64 mm) Clearance To Back Splash 13 1/2" (343 mm) 13 3/8" (340 mm) 8 1/4" **←**(210 mm) 8 9/16" (217 mm) € 8 1/4 (210 mm) → 15 3/8" (391 mm) 10 7/8" (276 mm) 10 7/16" (265 mm) 10 7/8" (276 mm) 2 1/4" (57 mm)

▲ Designate proper finish suffix

BRIZO

KITCHEN FAUCETS

- Litze[™] Collection
- Two Handle Widespread Bridge

STANDARD SPECIFICATIONS:

- Maximum 1.8 gpm @ 60 psi, 6.8 L/min @ 414 kPa
- Two or three hole mount
- Ceramic cartridge
- Spout rotates 360°
- Solid brass with one-piece brass waterway
- Lever handles

WARRANTY

- Lifetime limited warranty on parts (other than electronic parts and batteries) and finishes: or, for commercial users, for 5 years from date of purchase.
- 5 year limited warranty on electronic parts (other than batteries); or, for commercial users, for 1 year from the date of purchase. No warranty is provided on batteries.

COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1
- ASME A112.18.6

Indicates compliance to ICC/ANSI A117.1

 Verified compliant with .25% weighted average Pb content regulations.

