



# ▲ Designate proper finish suffix

Delta reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.deltafaucet.com for finish options and product availability.



see what Delta can do

# BATHROOM FAUCET

- Cassidy<sup>™</sup> Bath Collection
  Two Handle Widespread Pull-Down **Deck Mount**

# **FEATURES:**

- DIAMOND Seal® Technology
- MagnaTite<sup>®</sup> Docking

# **STANDARD SPECIFICATIONS:**

- Max. flow rate 1.2 gpm @ 60 psi, 4.5 L/min @ 414 kPa
- · Three hole mount
- · Solid brass fabricated end valve
- 1/4 turn stops
- Hot and cold stems are interchangeable
- Diamond coated ceramic cartridge
- 3/8" O.D. straight PEX supply tubes
- Models have metal drain with pop-up type fitting with plated flange and stopper
- · Not applicable for pedestal sink
- The hose can be pulled out for 20" maximum length

# **WARRANTY**

- · Parts and Finish Lifetime limited warranty; or for commercial purchasers, 10 years for multi-family residential (apartments and condominiums) and 5 years for all other commercial uses, in each case from the date the product is received by the original purchaser or their authorized representative (installation contractor, etc.).
- Electronic Parts and Batteries (if applicable) 5 years from the date the product is received by the original purchaser or their authorized répresentative (installation contractor, etc.); or for commercial purchasers, I year from the date the product is received by the original purchaser or their authorized representative (installation contractor, etc.). No warranty is provided on batteries.



# **COMPLIES WITH:**

- ASME A112.18.1 / CSA B125.1 ASME A112.18.2 / CSA B125.2
- Indicates compliance to ICC/ANSI A117.1 Valve control only
- EPA WaterSense®

**Delta Faucet Company** 55 E. 111th Street, Indianapolis, IN 46280 350 South Edgeware Road, St. Thomas, ON N5P 4L1 © 2023 Delta Faucet Company