

Commercial Flushometer Floor-Mounted Toilet – 1.0 GPF

FEATURES

- Floor-mounted
- Elongated front bowl
- Optional CeFiONtect™ glaze prevents debris from sticking to ceramic surfaces, making them easier to clean
- Clear glazed trapway coating
- 10"-12" rough-in

MODELS

- CT705UNG
Commercial, floor-mounted toilet with CeFiONtect ceramic glaze
- CT705UN
Commercial floor-mounted toilet

ADDITIONAL ITEMS

- SC534 seat
- SC134 seat

ECOPOWER® FLUSH VALVES	
Exposed	
TET1UA32#CP	1.0 GPF
Exposed 24" Breaker	
TET6UA32#CP	1.0 GPF
Concealed 14" x 12"	
TET2UA32#CP	1.0 GPF
Concealed 4" x 4"	
TET3UA32#SS	1.0 GPF

COLORS/FINISHES

- Standard
#01 Cotton



Flush valve sold separately



PRODUCT SPECIFICATION

The floor-mounted, low consumption siphon jet flushing toilet shall be 1.0 GPF (3.8 LPF) when paired with a 1.0 GPF flush valve. Toilet shall have optional CeFiONtect ceramic glaze. Toilet shall be TOTO Model CT705UN_____.

CODES/STANDARDS

- Meets and exceeds ASME A112.19.2/CSA B45.1
- Certifications: IAPMO(cUPC), State of Massachusetts, City of Los Angeles, and others
- Code compliance: UPC, IPC, NSPC, NPC Canada, and others



CT705UN(G)

Commercial Flushometer Floor-Mounted Toilet – 1.0 GPF

SPECIFICATIONS

Water Use	1.0 GPF (3.8 LPF)
Flush System	Siphon Jet Flushing Action
Water Surface	10-3/4" x 9-1/4"
Water Pressure	Min: 35 psi (Flowing) Max: 80 psi (Static)
Min. Flow Rate	24 GPM
Trap Diameter	1-7/8"
Trap Seal	2-3/8"
Rough-in	12" or 10"
Material	Vitreous China
Warranty	One Year Limited Warranty
Shipping Weight	50 lbs
Shipping Dimensions	26-1/2"L x 9-1/2" W1 x 16-1/4"W2 x 17"H

INSTALLATION NOTES

Spuds are unique for TOTO product. For replacement spuds, contact TOTO for part number THU073R.

Can be used with exposed or concealed top inlet flush valves.

DIMENSIONS

