dyson airblade V

TECHNICAL SPECIFICATION





REAR ELEVATION SIDE ELEVATION 91/4" 71/2" Fixing locations (4) Rear cable entry point Side cable entry point Side cable 151/2", 151/2" entry point Fixing locations (4)Ζ See table for recommended mounting heights All dimensions shown in inches (+/- 3/16 inch)

Recommended installation heights from floor					
Male	X 521/8"	Y 51 ³ / ₁₆ "	Z 365/8"		
Female	X 50 ³ / ₄ "	Y 49 ¹³ /16"	Z 35½"		
Child or disabled	X 42 ⁵ / ₁₆ "	Y 413/8"	Z 26 ¹³ / ₁₆ 1		
Child 5-8	X 37½"	Y 36 7/16"	Z 22"		
Child 8-11	X 417/16"	Y 40 ¹ / ₂ "	Z 25 ¹⁵ /16 ¹		
Child 11-14	X 44 ⁵ / ₈ "	Y 43 ⁵ / ₈ "	Z 29"		
Machine dimensions					
Height 151/2" Width 97/32" Depth 4"					

Minimum clearance			
81½" clearance either side and ½½" above machine.			
Cable entry point from floor			
Male	427/8"		
Female	411/2"		
Child or disabled	332/16"		
Child 5-8	281/4"		
Child 8-11	323/16"		
Child 11-14	351/4"		

dyson airblade V



Electrical

Input voltage/Frequency: 120-127 V 50&60 Hz Standby power consumption: Less than 0.5 W

Motor specification: 1,000 W digital brushless motor

Heater type: None

Construction

Fascia: Polycarbonate

Antibacterial coating type:

HU02 (Sprayed Nickel) contains antibacterial additive in paint.

HU02 (White) contains antibacterial moulded additive.

Can help prevent the growth of bacteria.

Back plate mounting bracket: ABS/PBT Plastic

Exterior screw type: Anti-tamper 4 mm Pin-Hex

Water ingress protection to IP24

Filter

HEPA filter (Glass fibre and fleece prelayer)

99.97% of particles captured to the size of 0.3 microns

Operation

Touch free capacitive sensor activation

Hand dry time measurement: 12 seconds (Measurement based on NSF Protocol P.335)

Sound power level: 79 dB (A)

Sound pressure level @ 2 m: 63 dB(A)1

Operation lock-out period: 30 seconds

Airspeed at aperture: 690 km/h / 430 mph

Maximum altitude: 2,000 metres / 6,561 ft.

Operating temperature range: 0°C-40°C / 32°F-104°F

Logistics

Single unit order code:

Sprayed Nickel: 307174-01, White: 307173-01

Unit barcode:

Sprayed Nickel: 885609009933, White: 885609009896

Net weight: 2.9 kg / 6.17 lbs

Packaged weight: 4.0 kg / 8.81 lbs

Packaged dimensions:

 $(H)145 \times (W)455 \times (D)274 \text{ mm} / (H)5^{3}/_{4}" \times (W)17^{7}/_{8}" \times (D)10^{3}/_{4}"$

Standard warranty

5 year warranty

¹Sound pressure measured at 2 m distance, in a semi-anechoic chamber.







The Carbon label is a trademark of the Carbon Trust. The NSF logo is the registered trademark of NSF International Quiet Mark is a registered trademark of the Noise Abatement Society.



Product range

Sprayed Nickel





