




Dimensions



 * $\,$ Distance from bottom of sink to center line of disposer outlet. Add 1/2" when stainless steel sinks are used.

** Length of tailpipe from center line of disposer outlet to end of tailpipe. NOTE: Plumb waste line to prevent standing water in disposer motor housing.

Job Specifications

STANDARD SERIES

Badger[®] 5

Submittal Sheet

This popular model offers the following features and benefits:

- Lift & Latch[™] technology for easier sink connection
- 1/2 Horsepower Heavy Duty Motor (Quiet Dura-Drive[®] Induction Motor)
- We Come To You® 3-Year In-Home Limited Warranty
- Rugged Galvanized Steel Construction (For Disposer Durability)
- Space-Saving Compact Design
- Available with or without a factory installed power cord.

Sample Specification

Food Waste Disposer(s) shall be InSinkErator Badger® 5, continuous feed, with 1/2 H.P. motor, galvanized steel grinding elements with two stainless steel 360° swivel lugs. Self-service wrench.

Available with or without a factory installed power cord.

Warranty:

3-Year parts and in-home service.

* The complete InSinkErator warranty is included in the Care & Use Booklet packed with each unit.



Food waste is roughly 80% water. By using your disposal regularly, you can help divert food waste from landfills and reduce greenhouse gas emissions. Make sustainability a family affair by using your disposal. After all, the smallest changes can make the biggest impact.





The Emerson logo is a trademark and service mark of Emerson Electric Co. The mounting collar configuration is a trademark of Emerson Electric Co.

InSinkErator may make improvements and/or changes in the specifications at any time, in its sole discretion, without notice or obligation and further reserves the right to change or discontinue models.

1-800-558-5700 www.insinkerator.com

Specifications

Continuous

Wall Switch

1/2

120

60

1725

6.3

Single Phase

Intermittent

Condor Grev

11-1/2"

26 oz. Manual Reset Overload

Permanently Lubricated Upper &

Approx. 1 Gallon per Person Per Day

3-4 KWh per Year

1-1/2" Cushioned

Available with or without

Slip Joint

Yes

13 lbs. 10 oz. (without cord) 13 lbs. 14 oz. (with cord)

Lower Bearings

Type of Feed

Motor

HP

ΗZ

Volts

RPM

On/Off Control

Amp. (Avg. Load)

Shipping Weight (Approx.)

Time Rating

Lubrication

Unit Finish

Capacity

Motor Protection

Average Water Usage

Dishwasher Drain Connection

Power Cord

Drain Connection

Average Electrical Usage

Factory Installed

Overall Height

Grind Chamber