

23 824

## LINEARE™

SINGLE HOLE SINGLE-HANDLE XS-SIZE  
BATHROOM FAUCET 4.5 L/MIN (1.2 GPM)

Pure Freude  
an Wasser



### STANDARD SPECIFICATION:

- GROHE SilkMove®
- GROHE StarLight®
- GROHE EcoJoy™
- GROHE QuickFix® Plus installation
- GROHE AquaGuide adjustable aerator 20°-40°
- 7 3/8" Faucet height (open position)
- 6 1/8" Faucet height (closed position)
- 4 3/16" Spout reach
- 3 3/4" Aerator height
- Solid brass construction with metal lever
- 23 1/2" Nylon braided flex hoses
- CALGreen/CEC compliant
- 4.5 L/min (1.2 gpm) (WaterSense)



### PRODUCT FEATURES:



-  GROHE StarLight®
-  GROHE SilkMove®
-  GROHE EcoJoy™
-  GROHE QuickFix®

### CERTIFICATIONS:



- ADA
- WaterSense
- CEC Certified
- Low Lead Certified
- CALGreen Compliant
- Energy Policy Act of 1992
- NSF 61
- NSF 372
- CSA B125.1
- ASME A112.18.1
- Complies with lead plumbing laws

### AVAILABLE FINISHES:

- 2382400A**  GROHE StarLight® Chrome
- 23824ENA**  Brushed Nickel InfinityFinish™

NOTE: Install this product according to the installation guide. ADA, CSA compliant when installed to the specific requirements of these regulations.

Tel: 1.888.644.7643 Fax: 1.905.366.2071  
We reserve the right to make revisions without notice to product specifications.  
For the most current Specification Sheet, go to [www.grohe.ca](http://www.grohe.ca).  
09-21-2021

PART OF **LIXIL**

23 824

**LINEARE™**

SINGLE HOLE SINGLE-HANDLE XS-SIZE  
BATHROOM FAUCET 4.5 L/MIN (1.2 GPM)

Pure Freude  
an Wasser



**TECHNICAL DATA:**

Product Height	6-1/8 in
Product Length	6 in
Product Width	1-3/4 in
Fitting Spout Height	3-3/4 in
Fitting Spout Reach	4-3/16 in
Fitting Handle Height	6-1/8 in
GPM (Min)-GPM (Max)	4.5 L/min (1.2 gpm)°
Fitting No of Holes Required	1

