



# COMPACT CADET® 3 FloWise® ELONGATED RIGHT HEIGHT™ ONE PIECE TOILET

VITREOUS CHINA

# COMPACT CADET® 3 FloWise® ELONGATED RIGHT HEIGHT™ ONE-PIECE TOILET WITH SEAT

### **2403 128**

- Vitreous china
- Meets definition for HET (High Efficiency Toilet)
- High Efficiency (4.8 Lpf/1.07 gpf)
- Space saving compact design Elongated Right Height bowl fits in the same space as a round front toilet
- EverClean<sup>®</sup> surface inhibits the growth of stain and odor causing bacteria, mold, and mildew
- Featuring the Cadet®3 Flushing System
- One-piece design
- Elongated siphon action jetted bowl with 54 mm (2-1/8") trapway
- · Internal trapway area fully glazed
- Rim height at 419mm (16-1/2") for accessible application
- Includes colour-matched and design-matched solid plastic toilet seat and cover with slow-close hinges and EverClean® surface. Seat features unique sanitary seat lift tab
- Oversized 76mm (3") Flush Valve with Chemical Resistant Flapper
- 254 x 208mm (10 x 8") water surface
- 2 bolt caps
- Chrome Trip Lever
- 100% factory flush tested
- 5 year warranty

Nominal Dimensions: 724 x 394 x 724mm (28-1/2" x 15-1/2" x 28-1/2")

## **Compliance Certifications -**

#### **Meets or Exceeds the Following Specifications:**

- ASME A112.19.2M for Vitreous China Fixtures includes Flush Performance, Ball Pass Diameter, Trap Seal Depth and all Dimensions
- Certified in EPA WaterSense HET program
- CAN/CSA B45 series

To Be Specified

Colour:


Supply with stop:

● Wh finishe

 When installed so top of seat is 432 to 483mm (17" to 19") from the finished floor

MEETS THE AMERICAN DISABILITIES ACT GUIDELINES AND ANSI A117.1 REQUIREMENTS FOR ACCESSIBLE AND USEABLE BUILDING FACILITIES-CHECK LOCAL CODES.





#### NOTES:

THIS TOILET IS DESIGNED TO ROUGH-IN AT A MINIMUM DIMENSION OF 305MM (12") FROM FINISHED WALL TO C/L OF OUTLET. SUPPLY NOT INCLUDED WITH FIXTURE AND MUST BE ORDERED SEPARATELY.

SUPPLY NOT INCLUDED WITH FIXTURE AND MUST BE ORDERED SEPARATELY. \* DIMENSION SHOWN FOR LOCATION OF SUPPLY IS SUGGESTED.

FOR ADDITIONAL INFORMATION REFER TO INSTALLATION INSTRUCTIONS SUPPLIED. IMPORTANT: Dimensions of fixtures are nominal and may vary within the range of tolerance established by ANSI Standard A112.19.2

These measurements are subject to change or cancellation. No responsibility is assumed for use of superseded or voided pages.



