

Buy it for looks. Buy it for life.®

There is more than 1 version of this model. Page down to identify the version you have.

DESCRIPTION

- Metal construction with various finishes identified by suffix
- Duralock[™] quick connect installation
- · Pulldown spray with 68" braided hose
- 3/8" compression connections will accept standard ball nose connection for 3/8" tubing
- High arc spout provides height and reach to fill or clean large pots while the pulldown wand provides the maneuverability for cleaning or rinsing

OPERATION

- Lever style handle
- · Operates with less than 5 lbs. of force
- Operates in stream or spray mode in the pulldown or retracted position

FLOW

Flow is limited to 1.5 gpm (5.7 L/min) at 60 psi

CARTRIDGE

- 1255™ Duralast™ cartridge for Single-Handle Faucets
- · Engineered polymers, non-ferrous and stainless steel materials

STANDARDS

- Third party certified to IAPMO Green, ASME A112.18.1/CSA B-125.1 and all applicable requirements referenced therein including NSF 61/9 & 372
- Meets CalGreen and Georgia SB370 requirements
- Complies with California Proposition 65 and with the Federal Safe Drinking Water Act
- ADA for lever handle

 The backflow protection system in this device consists of two independently operating check valves, a primary and a secondary which prevent backflow


WARRANTY

 Lifetime limited warranty against leaks, drips and finish defects to the original homeowner
 10 year limited warranty when

used in a multifamily installation

5 year limited warranty when used

in a commercial installation Visit www.moen.com/support for complete details and limitations



(DO NOT SCALE)

Specifications



Kiran™ Single Handle High Arc Pulldown Kitchen Faucet

Models: 87599 series

NOTE: THIS FAUCET IS DESIGNED TO BE IN STALLED THROUGH 1, 2, 3 AND 4 HOLE, 1-1/2" (38mm) MIN. DIA. (1 HOLE FOR SOAP DISPENSER)



FOR MORE INFORMATION CALL: 1-800-BUY-MOEN



Buy it for looks. Buy it for life.®

DESCRIPTION

- Metal construction with various finishes identified by suffix
- Quick connect installation
- Pulldown spray with 68" braided hose
- 3/8" compression connections will accept standard ball nose connection for 3/8" tubing
- High arc spout provides height and reach to fill or clean large pots while the pulldown wand provides the maneuverability for cleaning or rinsing

OPERATION

- Lever style handle
- Operates with less than 5 lbs. of force
- Operates in stream or spray mode in the pulldown or retracted position

FLOW

Flow is limited to 1.5 gpm (5.7 L/min) at 60 psi

CARTRIDGE


- 1255™ Duralast™ cartridge for Single-Handle Faucets
- Engineered polymers, non-ferrous and stainless steel materials

STANDARDS

- Third party certified to IAPMO Green, ASME A112.18.1/CSA B-125.1 and all applicable requirements referenced therein including NSF 61/9
- Meets CalGreen and Georgia SB370 requirements
- Complies with California Proposition 65 and with the Federal Safe Drinking Water Act
- ADA (for lever handle

The backflow protection system in this device consists of two independently operating check valves, a primary and a secondary which prevent backflow

WARRANTY



10 year limited warranty when used in a multifamily installation

Visit www.moen.com/support for complete details and limitations

5 year limited warranty when used in a commercial installation 17" (432mm) 2-1/2" (64mm) Max Deck Thickness 9-5/16

CRITICAL DIMENSIONS (DO NOT SCALE)

Specifications



Kiran™ **Single Handle High Arc Pulldown Kitchen Faucet**

Models: 87599 series

NOTE: THIS FAUCET IS DESIGNED TO BE IN STALLED THROUGH 1, 2, 3 AND 4 HOLE, 1-1/2" (38mm) MIN. DIA. (1 HOLE FOR SOAP DISPENSER)



FOR MORE INFORMATION CALL: 1-800-BUY-MOEN