
Sanipit®

Retrofit 1 HP grinder pump

Technical Sales Sheet

Saniflo **SFA**



MADE IN FRANCE TO SUPERIOR QUALITY STANDARDS

Since 1958, the legendary Sanibroyeur and its rich brand recognition is nestled in this Oise village on a more than 8 acres site. Daily, about 300 people get together and work hard to continue building its notoriety. Over the years, the Brégy site has seen important investments that has transformed this simple assembly line into a near-autonomous operation.

TESTING AND DESIGN



It's in the laboratory that the SFA products are designed and come to life. Nothing beats a series of tests to make sure the products are

WINDING AND MOTOR MANUFACTURING



SFA has integrated winding and motor assembly since 1960. Entirely under robot control, a digital camera controls part of the elements to ensure optimal effective and durable. quality every step of the wav.

MANUFACTURING PRODUCTION OF **OF ELECTRONIC BOARDS**



In the interest of superior quality, in the last few years, SFA integrated the production of its electronic boards at the Bréav site. These boards are then assembled by the operators.

COMPOSITE AND RUBBER PARTS




To date, the plastics processing department consists of 33 machines and a total of 760 molds. From the flow of the plastic pellets from the silos to the machines, to the melting and molding of the parts, the process is fully automated.

COMPONENTS ASSEMBLY



On site, robots and humans work together towards a common objective. When the work requires finesse, operators assemble parts, but when parts are difficult to move or assemble, robots come to the rescue.



Sanipit®24GR







Scan to

Pre-assembled

heavy-duty retrofit insert that **easily fits**

24" basins*.

Easy access to all major internal components including motor, grinder blade – and pressure switches.

Powerful 1 HP motor equipped with stainless steel grinder blade meant for residential and commercial applications.



Capable of pumping up to 25 Ft

(Max. Shut-off head: 33 Ft).

Equipped with

an external control panel

and visual/audible

alarm system.

Tight seal odour eliminating lid attaches with bolts into an interlocking channel.

fail-proof air pressure switch system with triple redundancy.

Superior wastewater
detection system
giving a longer life
expectancy without
any maintenance.

TECHNICAL SPECIFICATIONS

Motor/Electrical:

1 HP / 120 V - 60 Hz / 10 Amps (Max)

Max. temperature:

158 °F (70 °C)

Discharge/vent pipe diameters:

2" Discharge / 2" Vent

Discharge rate at 25 ft:

29 GPM (110 LPM)

Discharge rate at 3 ft:

66 GPM (250 LPM)

Shut-off head:

33 ft (10m)

Weight:

44 lbs (20 kg)

ON/OFF Levels:

7-3/4" (195mm) / 3-1/4" (83mm)

⊕

IP rating:

IP 68

Capacitor rating:

60 uF

Maximum vertical discharge:

25 ft (7.2 m)


Maximum horizontal discharge:

328 ft (100 m)

Basin capacity volume:

21 g (80 l)

PUMP CURVE




DIMENSIONS


PUMP KIT








CONTROL PANEL





ALARM PANFI





ALSO AVAILABLE FOR NEW INSTALLS Sanipit® 24 GRCB Part# 054

A pre-assembled packaged 24" x 24" grinding 1 HP pump system w/ basin and control panel/alarm system.





