KONCEPT EVO™ 60[™]



DR1790/DR1793 60" Rectangular Sliding Door

SPECIFICATIONS

Features

- Frameless sliding shower door for alcove shower
- Ultra-smooth rolling system
- Fixed panel in clear tempered glass of 10 mm (3/8") • and mobile panel in clear tempered glass of 8 mm (5/16")
- Glasses with Duraclean treatment for easy maintenance •
- Hidden anti-jump system without friction
- Strong rail with inner integrated stopper for a refined look •
- Padded magnetic seals for an pairtight seal and sound absorption
- Removable central guide for easy maintenance .
- 1956 mm (77") panel height provides freedom of movement
- Door access: 595 to 695 mm (23 1/2" to 27 1/2")
- 263 mm (10 3/8") refined handle style (exterior handle)
- 60 mm (2 3/8") minimum threshold required
- Reversible unit

Finish

Chrome[.]

- DR1790-110-XXX DR1793-110-XXX Matte black: - DR1790-160-XXX

DR1793-160-XXX

DR1790-110-003, DR1793-110-003; Right-opening shown




Glass pattern Clear tempered glass:

DR1793-XXX-003

This door can be installed with the following Kalia shower base(s) model(s); • BW1213 • BW1107 • BW1228 • BW1079 • BW1458 • BW1457 • BW1414 • BW1415 • BW1282 • BW1097

• BW1096





INSTALLATION NOTES

Minimum threshold required for installation is 60 mm (2 3/8"). This product must be installed following the installation instructions provided.

WARRANTY

Kalia Inc. guarantees all aspects of its products to be free of defects in material and workmanship for normal residential use. Refer to the warranty included with the Kalia products for details.

mm (77') mm (72 5/8" 956 448 595 mm å/to 695 mm 23 1/2" å/to 695 mm 1/2" å/to 27 1/2") 1422 mm å/to 1524 mm (56° å/to 60°) Important: Dimensions are approximated and are subject to changes. Please refer to the installation



instructions

1355, 2nd Street, Industrial Park Sainte-Marie (Québec) Canada G6E 1G9

T 418-387-9090 1-877-GO-KALIA (1-87-465-2542) F 418 387-9089

