




Company name: Waywest Mech.

Created by:

Phone:

Date:

11/14/2018

Position	Count	Description
	1	<p>UPS 26-99 FC</p>  <p>Product photo could vary from the actual product</p> <p>Product No.: 52722512</p> <p>The pump is of the canned rotor type, i.e. pump and motor form an integral unit without shaft seal and with only two gaskets for sealing. The bearings are lubricated by the pumped liquid. The pump is characterized by:</p> <ul style="list-style-type: none"> * Ceramic shaft and radial bearings. * Carbon axial bearing. * Stainless steel rotor can and bearing plate. * Corrosion-resistant impeller, Composite, PES. * Cast iron pump housing. <p>The motor is a 1-phase motor. No additional motor protection is required.</p> <p>Liquid:</p> <p>Pumped liquid: Water</p> <p>Liquid temperature range: 35.6 .. 230 °F</p> <p>Liquid temperature during operation: 140 °F</p> <p>Density: 61.35 lb/ft³</p> <p>Technical:</p> <p>Approvals on nameplate: UL, CSA</p> <p>Materials:</p> <p>Pump housing: Cast iron EN-JL1030 ASTM 30 B</p> <p>Impeller: Composite, PES</p> <p>Installation:</p> <p>Maximum ambient temperature: 104 °F</p> <p>Ambient max at 176°F liquid: 176 °F</p> <p>Maximum operating pressure: 145 psi</p> <p>Flange standard: USA Oval</p> <p>Type of connection: C.I. Flange</p> <p>Pipe connection: 2 - Bolt Flange</p> <p>Pressure stage: 10</p> <p>Port-to-port length: 6 1/2 in</p> <p>Electrical data:</p> <p>Power input in speed 1: 201150 HP</p> <p>Power input in speed 2: 179 W</p> <p>Max. power input: 197 W</p> <p>Main frequency: 60 Hz</p> <p>Rated voltage: 1 x 115 V</p> <p>Current in speed 1: 1.3 A</p>



Company name:

Created by:

Phone:

Date:

11/14/2018

Position	Count	Description
		Current in speed 2: 1.5 A Current in speed 3: 1.8 A Capacitor size - run: 20 μ F/180 V Number of poles: 2 Insulation class (IEC 85): F Others: Gross weight: 10.3 lb Country of origin: US Custom tariff no.: 8413.70.10.90

52722512 UPS 26-99 FC 60 Hz

